Destain Powder ALD03 **Product Revision date** 24 July 2017 Revision 1



Safety Data Sheet (SDS)

Section 1: Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name	Destain Powder ALD03
Product no.	ALD03
Synonyms, Trade names	No information available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Uses advised against	

Cleaning agent. Any other purpose.

1.3 Details of the supplier of the safety data sheet

Supplier	Manepa Hygenics 628B Jordanstown Avenue Greenogue Business Park Rathcoole Co. Dublin Tel: 014677600
Contact person	support@manepa.com
1.4 Emergency telephone number	
Emergency telephone	Emergency Telephone Number: 086 0272033 08:30 – 17:00 Monday to Thursday 08:30 – 16:30 Friday

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (EC 1272/2008)	
Physical and chemical hazards	Not classified
Human health	Acute Tox 4 - H302, Skin Corr. 1B - H314, Eye Dam. 1 - H318
Environment	Not classified

Danger

2.2 Label elements

Contains

disodium carbonate, compound with hydrogen peroxide (2:3) disodium metasilicate

Label in accordance with (EC) no. 1272/2008



Signal word

Hazard statements

H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage.

Precautionary statements

Prevention P260 Do not breathe dust/fume/ gas/mist/vapours/spray. Response P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P363 Wash contaminated clothing before reuse.

2.3 Other hazards

None known.

Section 3: Composition/identification of ingredients

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product identifier	Reg. EU 1272/2008	%
	CAS-No.: 15630-89-4 EC No.: 239-707-6	Acute Tox 4 - H302, Eye Dam. 1 - H318, Ox Sol 3- H272	30-60%
Idisodium metasilicate	CAS-No.: 6834-92-0 EC No.: 229-912-9	Skin Corr. 1B - H314, STOT SE 3 - H335	10-30%
sodium carbonate	CAS-No.: 497-19-8 EC No.: 207-838-8 REACH Reg No.: 01-2119485498-19-0000	Eye Irrit.2A - H319	10-30%
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts	CAS-No.: 68439-57-6 EC No.: 270-407-8	Skin Irrit.2 - H315, Eye Irrit.2A - H319, Aquatic Chronic 2 - H411	0.1-1%

The full text for all hazard statements are displayed in section 16.

Composition comments

The data shown are in accordance with the latest EC Directives.

Section 4: First aid measures

4.1 Description of first aid measures

General information	As a general rule, in case of doubt or if symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during rescue. Provide general first aid, rest, warmth and fresh air.
Inhalation	If inhaled, remove to fresh air. Keep person warm and at rest. If breathing is difficult, give oxygen. If not breathing, give artificial respiration and seek medical attention.
Ingestion	If this product is ingested, remove victim immediately from source of exposure. Rinse mouth thoroughly. Seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination Remove contaminated clothing. In case of skin contact flush exposed area with copious amounts of water. Continue to rinse for at least 15 minutes. Get medical attention if irritation develops or persists.
Eye contact	Do not rub eye. Avoid contaminating unaffected eye. Rinse with a gentle stream water for at least 15 minutes. Hold eye lids open. Remove contact lenses if present and easy to do so. Get prompt medical attention.

4.2 Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Inhalation of product dust may cause irritation to respiratory tract.
Ingestion	May cause chemical burns in mouth and throat. Harmful if swallowed.
Skin contact	Corrosive! Can cause redness, pain, and severe skin burns.
Eye contact	Causes severe eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to the physician	Treat symptomatically.
------------------------	------------------------

Section 5: Fire-fighting measures 5.1 Extinguishing media Extinguishing media Use fire-extinguishing media appropriate for surrounding materials. Water spray or CO2. Unsuitable extinguishing media Do not use dry chemicals or foams. 5.2 Special hazards arising from the substance or mixture Hazardous combustion products During fire, toxic gases (CO, CO2) are formed. May produce oxygen if heated to decomposition. Unusual fire & explosion hazards Slowly decomposes at temperatures exceeding 50°C forming sodium carbonate and hydrogen peroxide. Dust clouds may be explosive. Decomposition is accelerated by heat and may be accompanied by evolution of oxygen, which **Specific hazards** may enhance the combustion of other flammable materials. Containers can burst violently when heated, due to excess pressure build-up. **5.3 Advice for firefighters** Special fire fighting procedures Ventilate closed spaces before entering them. Keep up-wind to avoid fumes. Avoid breathing fire vapours. If possible, fight fire from protected position. Protective equipment for firefighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions For emergency responders	Eliminate all sources of ignition. Read and follow manufacturer's recommendations. Avoid prolonged or repeated exposure. In case of inadequate ventilation, use respiratory protection. Do not touch or walk through spilled material. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of dust or vapours and contact with skin and eyes. Avoid raising powdered materials into airborne dust. Follow safe handling advice and personal protective equipment recommendations for normal use of product.
6.2 Environmental precautions	
Environmental precautions	Avoid release to the environment.
6.3 Methods and material for contain	nment and cleaning up
Spill clean up methods	Prevent further leakage or spillage if safe to do so. Ventilate and evacuate the area. Eliminate all ignition sources. Wear necessary protective equipment. Wear respirator if ventilation is not adequate. Sweep/shovel up residues. Take care not to raise dust. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.
6.4 Reference to other sections	
Reference to other sections	For waste disposal, see section 13. See section 1 for emergency contact. For personal protection, see section 8.
Section 7: Handling and storage	
7.1 Precautions for safe handling	
Handling	Avoid inhalation of dust and contact with skin and eyes. Use personal protective equipment, see Section 8. Ensure good dust ventilation during handling. Wear appropriate respirator when ventilation is inadequate. Keep away from heat, sparks and open flame. Keep away from flammable materials and incompatible substances. Avoid generation of dust clouds/accumulation of dust in work area.

Never return spilled product into its original container for re-use. (Risk of decomposition).

7.2 Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from incompatible materials (see section 10).
Storage class	Corrosive storage. Store separately from other chemicals.
7.3 Specific end use(s)	
Specific end use(s)	The identified uses are in section 1 of this Safety Data Sheet.
Usage description	Use only according to directions. Replace and tighten cap after use.

Section 8: Exposure controls/Personal protection

8.1 Control parameters

Ingredient comments

No exposure limits noted for ingredient(s).

8.2 Exposure Controls



Respiratory equipment	136/140/145/143/149. The specific respirator selected must be based on contamination levels
	found in the work place. Where risk assessment shows air-purifying respirators are
	appropriate a full face respirator conforming to EN143 should be used, and suitable
	respirator cartridges as a backup to engineering controls. Use respiratory protective
	components with combined A/P filter(s) for organic vapours/particulates. Consult
	manufacturer for specific advice.
Hand protection	Where hand contact with the product may occur the use of gloves approved to relevant
Hand protection	standards (e.g. Europe: EN374) is recommended. (EU Directive 89/686/EEC). Gloves must be
	inspected prior to use. Suggested material: PVC. Natural rubber. Layer thickness: 0.11 mm.
	Breakthrough time: >480 minutes. Consult manufacturer for advice.
	Selection of the glove material depends on consideration of the penetration times, rates of
	diffusion and degradation, and concentration specific to the workplace. Use proper glove
	removal technique (without touching glove's outer surface) to avoid skin contact with this
	product. Dispose of contaminated gloves after use in accordance with applicable laws and
	good laboratory practices.
Eye protection	Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment
	for eye protection tested and approved under appropriate government standards such as EN
o.,	166(EU).
Other protection	Wear appropriate clothing to prevent skin contact. The selected clothing must satisfy the
	European norm standard EN 943. Personal protective equipment for the body should be
	selected based on the task being performed and the risks involved and should be approved
	by a specialist before handing this product.
Hygiene measures	Observe normal hygiene standards. Wash promptly if skin becomes contaminated. When
D 194	using do not eat, drink or smoke. Wash hands after use.
Process conditions	Ensure that eye flushing systems and safety showers are located close by in the work place.

Section 9: Physical and chemical properties

<u>9.1 Information on basic physical and chemical properties</u>

Appearance Colour Odour	Powder. White. No information available.
Odour threshold - lower	No information available.
Odour threshold - upper	No information available.

pł	pH-Value, Conc. Solution 12.50	
pł	H-Value, Diluted solution	No information available.
М	lelting point	No information available.
Initial boiling point and boiling range		No information available.
Flash point		No information available.
Ev	vaporation rate	No information available.
Fl	ammability state	No information available.
Fl	ammability limit - lower(%)	No information available.
Flammability limit - upper(%) No information available.		No information available.
Va	apour pressure	No information available.
Va	apour density (air=1)	No information available.
Re	elative density	No information available.
В	ulk density	No information available.
So	olubility	Soluble in water.
De	ecomposition temperature	No information available.
	artition coefficient; n- ctanol/Water	No information available.
Αι	uto ignition temperature (°C)	No information available.
Vi	iscosity	No information available.
Ех	xplosive properties	Not classified as explosive.
02	xidising properties	No information available.
<u>9.2 Oth</u>	ner information	
М	lolecular weight	No information available.
Vo	olatile organic compound	No information available.
Ot	ther information	None noted.
	- 10 CL-1911	
	1 10: Stability and reactivity eactivity	
	eactivity	Stable under recommended transport and storage conditions and under recommended use.
	<u>nemical stability</u>	Stable under normal temperature conditions and recommended use
51	tability	Stable under normal temperature conditions and recommended use.
	ossibility of hazardous reactions	
Ha	azardous reactions azardous polymerisation olymerisation description	Contains SODIUM PERCARBONATE:Avoid contact with metals, metallic ions, alkalis, reducing agents and organic matter (e.g. alcohol, terpenes) as this may produce self- accelerated thermal decomposition. Dust clouds may be explosive. No information available. Unknown

Polymerisation description

Unknown.

10.4 Conditions to Avoid		
Conditions to avoid	Heat, sparks, open flames, temperature extremes and direct sunlight. Slowly decomposes at temperatures exceeding 50°C forming sodium carbonate and hydrogen peroxide.	
10.5 Incompatible materials		
Materials to avoid	Contains SODIUM PERCARBONATE:Avoid contact with metals, metallic ions, alkalis, reducing agents and organic matter (e.g. alcohol, terpenes) as this may produce self- accelerated thermal decomposition. Sodium percarbonate in water rapidly dissociates into hydrogen peroxide and sodium carbonate. Do not mix with other chemicals unless listed on directions.	
10.6 Hazardous decomposition products		
Hazardous decomposition products	In case of fire, toxic gases (CO, CO2,) may be formed. When heated, vapours/gases hazardous to health may be formed. Sodium carbonate. Hydrogen peroxide. Oxygen.	
Section 11: Toxicological information		
11.1 Information on toxicological effects	i	
Toxicological information	Harmful if swallowed.	
Acute toxicity (Oral LD50)	DISODIUM METASILICATE (CAS: 6834-92-0): 994 mg/kg, Rat. REACH dossier information.	
Acute toxicity (Dermal LD50)	SODIUM CARBONATE (CAS: 497-19-8): 2800 mg/kg, Rat. REACH dossier information. DISODIUM METASILICATE (CAS: 6834-92-0): > 3000 mg/kg Rat. REACH dossier information. SODIUM CARBONATE (CAS: 497-19-8): > 2000 mg/kg, Rabbit. REACH dossier information.	
Acute toxicity (Inhalation LD50)	DISODIUM METASILICATE (CAS: 6834-92-0): > 2.06 mg/l (vapours) Rat. REACH dossier information. SODIUM CARBONATE (CAS: 497-19-8): 2300 mg/m ³ (aerosol) Rat, 2 hours. REACH dossier information.	
Serious eye damage/irritation	Causes serious eye damage.	
Skin corrosion/irritation	No information available.	
Respiratory sensitisation Skin sensitisation	No information available. No information available.	
Germ cell mutagenicity	No information available.	
Carcinogenicity	No information available.	
Specific target organ toxicity - Single exposure:STOT - Single exposureNo information available.Specific target organ toxicity - Repeated exposure:STOT - Repeated exposureNo information available.		
Inhalation Ingestion Skin contact Eye contact Waste management	Inhalation of product dust may cause irritation to respiratory tract. May cause chemical burns in mouth and throat. Harmful if swallowed. Corrosive! Can cause redness, pain, and severe skin burns. Causes severe eye damage. When handling waste, consideration should be made to the safety precautions applying to handling of the product.	
Routes of entry Target organs	No information available. Eyes, skin, digestive system, respiratory system.	
Aspiration hazards: Reproductive toxicity:	No information available. No information available.	

Name	LD50 oral	LD50 dermal	LD50 inhalation
sodium carbonate	2800.00mg/kg Rat 2800.00mg/kg Rat	>2000.00mg/kg Rat 2000.00mg/kg Rat	
Silicic acid, sodium salt	>2000.00mg/kg Rat		

Section 12: Ecological information		
12.1 Toxicity		
Acute toxicity - Fish	Disodium Metasilicate (CAS: 6834-92-0): LC50 (96 hours) 210 mg/l, Brachydanio rerio, (Zebra Fish.) REACH dossier information. SODIUM CARBONATE (CAS: 497-19-8): LC50 96	
hours 300 mg/l Lepomis macrochirus (Bluegill.) REACH dossier information. Acute toxicity - Aquatic invertebrates Disodium Metasilicate (CAS: 6834-92-0): EC50 (48 hours) 7.8 pH, Daphnia magna. dossier information. SODIUM CARBONATE (CAS: 497-19-8): EC50 (48 hours) 200 Ceriodaphnia sp. REACH dossier information.		
Acute toxicity - Aquatic plants	Disodium Metasilicate (CAS: 6834-92-0): EC50 (72 hours) 207 mg/l, Desmodesmus subspicatus. REACH dossier information.	
Acute toxicity - Microorganisms	No information available.	
Chronic toxicity - Fish	No information available.	
Chronic toxicity - Aquatic invertebrates	No information available.	
Chronic toxicity - Aquatic plants	No information available.	
Chronic toxicity - Microorganisms	No information available.	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Eco toxilogical information	The product is not classified as dangerous for the environment.	
12.2 Persistence and degradability		
Degradability Biological oxygen demand Chemical oxygen demand	The degradability of the product has not been stated. No information available. No information available.	
12.3 Bioaccumulative potential		
Bioaccumulative potential Bioacculmation factor Partition coefficient; n- Octanol/Water	No data available on bioaccumulation. No information available. No information available.	

12.4 Mobility in soil

Mobility

Soluble in water.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment The product does not contain any PBT or vPvB substances.

None known.

12.6 Other adverse effects

Other adverse effects

Name	Acute toxicity (Fish)	Acute toxicity (Aquatic invertebrates)	Acute toxicity (Aquatic plants)
sodium carbonate		EC50 48 Hours 265.00mg/l Daphnia magnaEC50 48 Hours 265.00mg/l Daphnia magna	
	LC50 96 Hours 3185.00mg/l Brachydanio rerio (Zebra Fish)	EC50 48 Hours 4857.00mg/l Daphnia magna	

Section 13: Disposal consideration	\$
Waste management	When handling waste, consideration should be made to the safety precautions applying to handling of the product.
13.1 Waste treatment methods	
Disposal methods	Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations. For waste disposal, use a licensed industrial waste disposal agent.

Section 14: Transport information

14.1 UN number

UN no. (ADR)	UN3262
UN no. (IMDG)	UN3262
UN no. (IATA)	UN3262

14.2 UN proper shipping name

ADR proper shipping name

IMDG proper shipping name

IATA proper shipping name

sodium salt) CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (disodium metasilicate + Silicic acid, sodium salt) CORROSIVE SOLID, BASIC, INORGANIC N.O.S. (disodium metasilicate + Silicic acid, sodium salt)

CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (disodium metasilicate + Silicic acid,

14.3 Transport hazard class(es)

ADR class	8
IMDG class	8
IATA class	8

Transport labels



14.4 Packing group

ADR/RID/ADN packing group IMDG packing group IATA packing group	III III III
14.5 Environmental hazards	
ADR	No
IMDG	No
IATA	No
14.6 Special precautions for user	
EMS	F-A, S-B
Emergency action code	A3
Hazard no. (ADR)	80
Tunnel restriction code	(E)

14.7 Transport in bulk according to annex II of MARPOL73/78 and the IBC code

Not applicable.

Section 15: Regulatory information

15.1 Safety, health and environmental regulations/Legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th May 2010 amending regulation (EC) No 1907/2006.
Approved code of practice	2016 Code of Practice for the Chemical Agents Regulations in accordance with section 60 of the Safety, Health and Welfare at Work Act 2005 (No. 10 of 2005).
	Workplace Exposure Limits Guidance Note EH40/2005.
Chemical safety assessment	No chemical safety assessment has been carried out.

Section 16: Other information

General information	This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.
Revision comments	This is a first issue.
Revision date	24 July 2017
Revision	1
Safety data sheet status	Approved.

Hazard statements in full

H272	May intensify fire; oxidiser.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H314	Causes severe skin burns and eye damage.
H335	May cause respiratory irritation.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H411	Toxic to aquatic life with long lasting effects.
H290	May be corrosive to metals.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.